

# Inspirations® Point-Of-Use



IB 215

IW 215

## Features

- High quality, high output refrigeration and heating systems
- Same internal components as the Reflections® family
- Solid, one-piece cabinet made from High Density Polyethylene is extremely durable and easy to clean
- No external base plate
- Energy Star rated 2.0L hot tank with On/Off switch
- Stainless steel cold reservoir
- Removable, two-piece, dishwasher safe drip tray
- Dual mechanical float for reliability
- Available in black or white
- UL certified

## Models

H&C: IB215, IW215

C&C: IB115, IW115



# Inspirations®

## Power

|                          |                     |
|--------------------------|---------------------|
| Voltage (V)              | 115, 220, 100       |
| Frequency (Hz)           | 50/60               |
| Power Consumption        | 4.89A / 554W / 115V |
| Cold Power Consumption   | 1.44A / 118W / 115V |
| Hot Power Consumption    | 3.87A / 449W / 115V |
| ES (KWH/24hrs)           | 1.14                |
| % lower than ES Standard | 5.0%                |

## Hot Water System

|   |                              |
|---|------------------------------|
| Avg. Hot Water Temp at nozzle @ 75°F ambient(Before/After On) | 166.57°F / 191.43°F          |
| Hot water ARI Rating  | 45 6oz > 165°F +/- 10%       |
| Hot Thermostat / Heat Limiter                                 | 203°F +/-5.5°F               |
| Hot Thermostat / Thermister Cycle                             | 167°F +/-11°F / 187°F +/-4°F |
| i-Boil Set Point  | N/A                          |
| Avg. Temp of i-Boil at nozzle @ 75°F ambient (After On)       | N/A                          |
| Hot Water Flow Rate   | 0.96 oz/sec                  |
| Hot Water Flow Rate (oz per sec)w/Accu-Temp delay             | N/A                          |
| Hot Tank Size (L)   | 2.0L                         |
| Heat Band Wattage   | 450W                         |

## Cold Water System

|   |                      |
|---|----------------------|
| Avg. Cold Water Temp at nozzle @ 75°F ambient(Before/After ON)  | 45.87°F / 42.2°F     |
| Cold Water ARI Rating   | 27 5oz < 50°F +/-10% |
| Cold Thermostat Set Point                                       | 45°F +3°/-8°F        |
| Cold Water Flow Rate  | 1.4 oz/sec           |
| Cold Water Flow Rate (oz per sec)w/ Accu-Temp delay             | N/A                  |
| Cold Tank Size / Usable Volume / Below Baffle Cold Water (Gal.) | 1 / 0.55 / 0.4 G     |

## Weights and Measurements

|   |                           |
|---|---------------------------|
| Net Weight (H&C / C&C Lbs.)                       | 34.6 / 31.68              |
| Gross Weight (H&C / C&C Lbs.)                     | 37.9 / 34.98              |
| Cooler Dimensions / Boxed Dimensions WxDxH (inch) | 12.4x13.5x39 / 13x13.9x40 |
| Container Load (20')                              | 224                       |
| Container Load (40')                              | 462                       |
| Container Load (40' HC)                           | 462                       |
| Container Load (45' HC)                           | 518                       |
| Certifications                                    | UL                        |